

**SILVYN® RILL PA 6****Non-Metallic Flexible Quick-Connect Conduit****Application Advantage**

- Halogen-free, flame retardant, and self-extinguishing
- Durable, long-lasting conduit is rugged yet flexible

**Approvals**

SILVYN® RILL PA 6 is a flexible, non-metallic corrugated conduit suitable for use in various industrial applications. It is resistant to liquids, oils, and gases, and highly resistant to acids and solvents. For use in controls, moving machine parts, motor and internal connections, and in industrial, medical, or electronic applications.

**Complete the Installation**

SILVYN®  
KLICK-G  
page 568



SILVYN®  
KLICK 90°  
page 569

**Technical Data**

<b>Material:</b>	Halogen- & silicone-free polyamide	<b>Color:</b>	Black (RAL 9005) Gray (RAL 7001)
<b>Temperature Range:</b>	-40°C to +115°C - Short-term: up to +150°C	<b>Approvals:</b>	V-0 per UL 94 RoHS

Part Number		Outer Diameter		Inner Diameter		Bend Radius		Conduit Coil Put-Ups (ft)	Thread Size for Fittings		
Black	Gray	(in)	(mm)	(in)	(mm)	(in)	(mm)		PG	NPT	Metric
61746935	61746939	0.394	10.0	0.256	6.5	0.512	13.0	164	PG 7	NPT ¼"	M10 x 1.0
61746945	61746940	0.512	13.0	0.394	10.0	0.787	20.0	164	PG 9	NPT ¼"	M12 x 1.5
61746955	61746950	0.622	15.8	0.472	12.0	1.378	35.0	164	PG 11	NPT ⅜"	M16 x 1.5
61747015	61747010	0.728	18.5	0.563	14.3	1.575	40.0	164	PG 13	—	—
61746965	61746960	0.835	21.2	0.650	16.5	1.772	45.0	164	PG 16	NPT ½"	M20 x 1.5
61746975	61746970	1.122	28.5	0.906	23.0	2.165	55.0	164	PG 21	NPT ¾"	M25 x 1.5
61746985	61746980	1.358	34.5	1.142	29.0	2.559	65.0	82	PG 29	NPT 1"	M32 x 1.5
61746995	61746990	1.673	42.5	1.417	36.0	3.543	90.0	82	PG 36	NPT 1¼"	M40 x 1.5
61747005	61747000	2.146	54.5	1.890	48.0	3.937	100.0	82	PG 48	NPT 1½"	M50 x 1.5