

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: **SIS-12-65-T**
Customer Part Number: SIS12T65-XXX

Description: 12 AWG(3.31 MM²) SIS 90 DEGC , 3173 XLPE 125 DEGC 600V, 65 OR 64 STRANDS TINNED

AWG: 12 Gauge

Conductor (Stranding): 65 X 30 AWG Tinned Copper, UL
Conductor OD (Nom) 0.089 inches
Max. Lay Length: 2.0 inch Lay
Min Avg Wall Thickness: 0.030 inches
Min. O.D : 0.150 inches
Nom. O. D: 0.153 inches
Circular Mils (CMA): 6399 (Min)
Strip Force 5 lbs (min) - 22 lbs (max)
Surface Print: 12 AWG (3.31 mm²) (UL) SIS 600V E7088 OR AWM STYLE 3173 XLPE 125C 600V CSA SIS 90C 600V FT2 OR CL1251 XLPE 125C 600V LL25850

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
Packard: N/A	Other: UL / CSA SUB 44	

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 6-3-2014
Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998