

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: **XHHW/SIS-F-12-1005**
Customer Part Number: SIS12T65-X

Description: 12 AWG(3.31mm²) XHHW-2 & SIS (VW-1) DUAL RATED, **EPCV**
SUPEROHM INSULATED 90 DEG C 600V, 65 STRANDS TINNED
WITH **c(UL)** MARKING

Conductor (Stranding): 65 X 30 AWG Tinned Copper , UL
Conductor OD (Nom) 0.089 inches
Max. Lay Length: 2.0 inch Lay
Min Avg Wall Thickness: 0.030 inches
Min. O.D : 0.149 inches
Nom. O.D: 0.152 inches
Max Runout: 0.008 inches
Strip Force: 5 lbs(min) –22 lbs(max)
Circular Mils (CMA): 6334 (Min)
Surface Print: 12 AWG (3.31mm²)(UL) XHHW-2 OR SIS VW-1 600V E7088 CSA **c(UL)**
R90 600V FT1 FT2 LL25850

This product is RoHS Compliant

Insulation Compound : EPCV Compound with excellent Heat, Radiation, Crush, Deformation Resistance at high temperatures and Superior Flexibility.

Passes Cold Bend Test @ Minus 40C for 4 Hours.

It is not Halogen Free.

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
Packard: N/A	Other: UL STD 44 / CSA 22.2#127-2009	

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)
Date: 7-2-2014