



Specification Sheet

Lake Cable Part #: RFH16(26)T-08

Description: 16 AWG 1 conductor 26 strand tinned copper with XLPE insulation, unshielded 600V cable, approved for use in RFH-2/FFH-2/XLPE, UL AWM 3320 and CSA AWM I A/B applications.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 16 AWG 26 Strands Class K
 - 1.2. Material: Annealed Tinned Copper
 - 1.3. Conductor Count: 1 Conductor

- 2. Insulation**
 - 2.1. Material: Cross-linked Polyethylene
 - 2.2. Wall Thickness: 0.030"
 - 2.3. Diameter: 0.115" ± 0.005"
 - 2.4. Color Code: Gray
 - 2.5. Weight: 14 lbs./Mft.

- 3. Assembly**
 - 3.1. Lay Length: N/A
 - 3.2. Fillers: N/A
 - 3.3. Binder: N/A
 - 3.4. Shield: N/A
 - 3.5. Drain Wire: N/A

- 4. Jacket**
 - 4.1. Material: N/A
 - 4.2. Wall Thickness: N/A
 - 4.3. Diameter: N/A
 - 4.4. Color: N/A
 - 4.5. Ripcord: N/A
 - 4.6. Weight: N/A

- 5. Markings**
 - 5.1. Type: Conductors shall be permanently identified via surface inkjet print
 - 5.2. Legend: LAKE CABLE E207518 (UL) RFH-2/FFH-2/XLPE 16AWG 600V 90°C AWM 3320 CSA AWM I A/B 90°C 600V FT2 226471 "ROHS COMPLIANT" MADE IN USA
 - 5.3. Footage Markers: No

- 6. Standards**
 - 6.1. Meets all requirements of UL Standard 66 for Type RFH-2/FFH-2
 - 6.2. Meets all requirements of UL AWM 3320 600V
 - 6.3. Meets all requirements of CSA AWM I A/B 600V
 - 6.4. Cable is RoHS III compliant per Directive 2015/863/EU
 - 6.5. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017
 - 6.6. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION