



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

COPPERFIELD[®] SIS

Construction Parameters:

CONDUCTOR: 14 AWG - 4/0 AWG stranded tinned copper
INSULATION: Flame-Retardant Cross-Linked Polyethylene (FR-XLPE)
COLORS: Black, White, Red, Orange, Yellow, Green, Blue, Brown, Gray, Violet, Green/Yellow
PRINT LEGENDS: XX AWG (X.XXmm²) E137925 (PLANT ID CODE) (UL) XHHW-2 OR SIS 90C 600V VW-1 --
14 AWG - 10 AWG 156016 CSA SIS 90C 600V -40C FT1 FT2 VW-1

PRINT LEGENDS: XX AWG (XX.Xmm²) E137925 (UL) XHHW-2 OR SIS 90C 600V VW-1 -- 156016 CSA
8 AWG - 4/0 AWG RW90 90C DRY/90C WET 600V PRI -40C FT1 FT4 OR SIS 90C 600V -40C FT1 FT2 VW-1

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 90°C Dry, 90C Wet

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

Industry Approvals:

- o ASTM B-33
- o UL 44 Type XHHW-2
- o CSA C22.2 No. 38 RWU90, SIS
- o CSA RW90, PRI, 600V (8 AWG & Larger)
- o Flame Tests: CSA FT1, FT2, VW-1, IEEE 383, FT4/IEEE 1202
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Nom. DCR Ω/1M'
				Inches	mm	Inches	mm	Lb./kft.	kg/km	
F14453	14	1	41/30	0.030	0.76	0.127	3.23	19	28	2.82
F12218	12	1	65/30	0.030	0.76	0.145	3.68	25	37	1.77
18810	10	1	104/30	0.030	0.76	0.166	4.22	41	61	1.11
18808	8	1	133/29	0.045	1.14	0.246	6.25	69	103	0.41
18806	6	1	133/27	0.045	1.14	0.277	7.04	105	156	0.41
18804	4	1	133/.0177	0.045	1.14	0.326	8.28	159	237	0.25
18802	2	1	133/23	0.045	1.14	0.394	10.01	243	362	0.17
18821	1/0	1	1064/30	0.055	1.40	0.477	12.12	563	838	0.10
18822	2/0	1	1330/30	0.055	1.40	0.517	13.13	717	1067	0.08
18823	3/0	1	1672/30	0.055	1.40	0.571	14.50	902	1342	0.07
18824	4/0	1	2109/30	0.055	1.40	0.654	16.61	1121	1668	0.05

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

* Ampacity values based on NEC Table 310.17 (8 AWG thru 4/0) 90°C. Larger sizes based on single conductor in free air, 30°C ambient and 90°C conductor temperature.

† Ampacity values based on CEC Table 1 (RW90) 90°C.

This product complies with European Directive 2011/65/EU (RoHS-2)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: September 24, 2013