

SIS XHHW-2

Construction:

Annealed bare or tinned stranded copper conductor insulated with a high grade XLPE.
 UL Listed, SIS 90°C Dry XHHW-2 90°C Dry 90°C Wet 600 Volts meets VW-1 UL 44.

Size	Stranding	Insulation Thickness	Nom O.D.	Std. Package	Shipping Weight ~lbs / 1000'
14	41/010	0.030	0.138	5000	19
12	65/010	0.030	0.156	5000	28
10	105/010	0.030	0.181	5000	43
8	7/19/0112	0.045	0.267	TBD	74
6	7/19/0140	0.045	0.302	TBD	107
4	7/19/0177	0.045	0.368	TBD	163
2	19/7/0223	0.045	0.434	TBD	243
1/0	19/56/010	0.080	0.575	TBD	422
2/0	19/70/010	0.080	0.627	TBD	504
3/0	19/88/010	0.080	0.682	TBD	620
4/0	19/111/010	0.080	0.747	TBD	773

- Special stranding and packaging available upon request.
- UL Listed

MADE IN THE USA

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926