

# SJOOW Flexible Cords and Cables

300 Volt, 90°C Flexible Cord. Heat, Moisture and Oil Resistant EPDM Rubber Insulation and Heat, Moisture and Oil Resistant Flexible CPE Jacket



PRODUCT DATA SHEET

SJOOW Flexible Cords and Cables are suitable for control equipment on machine tools subjected to medium mechanical stresses; for fixed or flexible installation, where free movement is required without tensile stresses and without forced guidance system; and in dry, damp and wet interiors— including water-oil mixtures.



## FEATURES

- Excellent resistance to oil and moisture
- Good tensile strength, elongation and aging characteristics
- High flexibility
- Excellent abrasion resistance
- Water-resistant\*
- UL Listed and CSA Certified for indoor and outdoor use
- Ozone, sunlight (UV) and weather-resistant

## CONSTRUCTION

**Conductor:** Stranded bare copper, Class K per ASTM B-174

**Insulation:** EPDM, oil resistant

**Fillers:** 2C/3C x18AWG: Rip Cord+ Cotton Yarn; others: PP Rope

**Separator:** Paper

**Jacket:** CPE, oil resistant

**Jacket Colour:** Black; additional colors available

**Print Legend:** ASCENT E486041 XXAWG XX/C SJOOW UL 300V(-40C-90C) CSA LL268042 FT-2 WATER RESISTANT P-07KA140001-MSHA—RoHS xxxxxFT

## PERFORMANCE STANDARDS

- UL Flexible Cord - UL 62
- CSA Standard - C22.2 No. 49
- CSA FT2 Flame Test
- MSHA Approved
- RoHS Compliant

## APPLICATIONS

- Machine tools, power tools
- Portable machinery
- Submersible pumps
- Motor leads

\*Suitable for immersion in water if properly sealed and terminated.

## COLOR CODE CHART

No. of Conductors	Color
2	Black, White
3	Black, White, Green
4	Black, White, Green, Red

Part Number	No. of Cond.	AWG	No. of Strands	Nom. Insul. Thickness		Nom. OD		Amps <sup>†</sup>
				Inch	mm	Inch	mm	
SJO18020W-0/90C	2	18	16/30	0.030	0.76	0.291	7.40	10
SJO18030W-0/90C	3	18	16/30	0.030	0.76	0.305	7.75	10
SJO18040W-0/90C	4	18	16/30	0.030	0.76	0.340	8.60	7
SJO16020W-0/90C	2	16	26/30	0.030	0.76	0.311	7.90	13
SJO16030W-0/90C	3	16	26/30	0.030	0.76	0.330	8.40	13
SJO16040W-0/90C	4	16	26/30	0.030	0.76	0.362	9.20	10
SJO14020W-0/90C	2	14	41/30	0.030	0.76	0.343	8.70	18
SJO14030W-0/90C	3	14	41/30	0.030	0.76	0.370	9.40	18
SJO14040W-0/90C	4	14	41/30	0.030	0.76	0.406	10.3	15
SJO12030W-0/90C	3	12	65/30	0.030	0.76	0.429	10.9	25
SJO12040W-0/90C	4	12	65/30	0.030	0.76	0.472	12.0	20

<sup>†</sup>Ampacities are based on NEC Table 400.5 (A)(1) at 30°C ambient in free air.

All trademarks are property of their respective owners. All specifications are subject to change.

<b>Design Number</b>	10026		
<b>Revision History</b>			
01	2019/04/23	Initial release	
Created T. Plochocki			
Approved A. Huang			

**Bristol** | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK  
**Frankfurt** | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf  
**Milwaukee** | 5001 South Towne Dr. New Berlin, WI 53151 USA  
**Suzhou** | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park, Jiangsu, China 215122

