



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

Royal® 300V SJOOW

Construction Parameters:

CONDUCTOR: 18 AWG - 10 AWG Class K stranded bare copper per ASTM B-174
INSULATION: EPDM
JACKET: CPE
COLOR: Black (Other colors available upon request)
PRINT LEGEND: SOUTHWIRE® ROYAL® (5 CROWN LOGO) CORD X/C XX AWG (X.XXmm2) SJOOW E46194 (UL) 300V -40C TO 90C -- CSA LL90458 SJOOW 300V -40C TO 90C FT2 WATER RESISTANT

INDENT LEGEND: P-07-KA070018-1-MSHA

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 90°C
WATER RESISTANT: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 300V rms, Max

Industry Approvals:

- o UL Standard 62
- o CSA Standard C22.2 No. 49
- o NEC Article 501.140 Class I Div. 2
- o NEC Article 400
- o Federal Spec JC580
- o Passes CSA FT2 Flame Test
- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	CCI Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		UL 62 O.D. Range	Net Weight		Amps*	Nom. DCR Ω/1M'	Color Code
					Inches	mm	Inches	mm		Lb./kt.	kg/km			
558116	823225	18	2	16/30	0.030	0.76	0.285	7.24	0.280" - 0.315"	37	55	10	6.59	Black, White
558117	823325	18	3	16/30	0.030	0.76	0.310	7.87	0.300" - 0.335"	49	73	10	6.59	Black, White, Green
558120	823425	18	4	16/30	0.030	0.76	0.330	8.38	0.325" - 0.365"	59	88	7	6.59	Black, White, Red, Green
558118	823226	16	2	26/30	0.030	0.76	0.310	7.87	0.305" - 0.340"	46	68	13	4.05	Black, White
558085	823326	16	3	26/30	0.030	0.76	0.330	8.38	0.325" - 0.360"	59	88	13	4.05	Black, White, Green
558119	823426	16	4	26/30	0.030	0.76	0.357	9.07	0.350" - 0.395"	73	109	10	4.05	Black, White, Red, Green
558121	823227	14	2	41/30	0.030	0.76	0.340	8.64	0.335" - 0.375"	60	89	18	2.55	Black, White
558086	823327	14	3	41/30	0.030	0.76	0.365	9.27	0.360" - 0.395"	79	118	18	2.55	Black, White, Green
558123	823427	14	4	41/30	0.030	0.76	0.395	10.03	0.390" - 0.435"	98	146	15	2.55	Black, White, Red, Green
560015	823228	12	2	65/30	0.030	0.76	0.410	10.41	0.405" - 0.455"	90	134	25	1.61	Black, White
558087	823328	12	3	65/30	0.030	0.76	0.430	10.92	0.425" - 0.475"	116	173	25	1.61	Black, White, Green
558124	823428	12	4	65/30	0.030	0.76	0.470	11.94	0.465" - 0.520"	150	223	20	1.61	Black, White, Red, Green
558378	823229	10	2	104/30	0.045	1.14	0.545	13.84	0.540" - 0.605"	155	231	30	0.98	Black, White
558125	823329	10	3	104/30	0.045	1.14	0.569	14.45	0.565" - 0.635"	200	298	30	0.98	Black, White, Green
558126	823429	10	4	104/30	0.045	1.14	0.635	16.13	0.625" - 0.700"	257	382	25	0.98	Black, White, Red, Green

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

* Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2011/65/EU (RoHS-2)
 The customer will accept all factory lengths and +/- 10 percent of total order requested.
 The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: June 23, 2014