



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 14-41 2/C CU SJTOW PAPER GRAY 300V

STOCK NUMBER: 56-47-06-01

JACKET:

NOMINAL OUTSIDE DIAMETER:	.340"	in.
NOMINAL WALL THICKNESS:	.030"	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	2	
CONDUCTOR COLOR ROTATION:	Black, White	
NOMINAL OUTSIDE DIAMETER:	.136"	in.
NOMINAL WALL THICKNESS:	.030"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	14 AWG 41X.010" SBC	

TEMPERATURE: 105°C - MAX
-40°C - MIN

FILLERS: Paperfiller

PACKAGE: 30" PLYWOOD REEL

PRINT: **INDENT**
(UL) VW-1 E46194 (M) SJTOW 2/C 14 AWG (2.08mm²) 60°C WATER RESISTANT
300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013