



Domtech Inc.
40 East Davis Street
Trenton, Ontario
Canada, K8V 6S4
Ph: 613-394-4884
Fax: 613-394-5372
Toll Free: 888-278-8258 (USA & Canada)
www.domtech.net

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

June 7, 2013

PART NUMBER: 1614TBA

DESCRIPTION: SJTW 14(41B)/2 60C POLY-P BLACK
.348",CC098(WHT-BLK),SMOOTH,INDENT IW479 WR,FT2,UL/CSA
30" PLY REEL-NR,1524M(5000FT)

CONDUCTOR: Stranded #14 awg 41x.0100" soft bare copper

INSULATION: Lead Free PVC .030" nominal thickness
DIAMETER: .136" +/- .002"

ASSEMBLY: Cabled with poly fillers and a 2.375" +/- 0.125" lay
Paper separator applied between core and jacket.

COLOUR SEQUENCE: Black-White

JACKET: Lead Free PVC .030" nominal thickness.
DIAMETER: .348" +/- .006"

TEMPERATURE: -40°C to 60°C

VOLTAGE: 300

FLAME RATING: FT2

PRINT TYPE: Indent
PRINT LEGEND: CSA LL39965 SJTW 2/C 2,08mm² (14 AWG) 60°C WATER RESISTANT
300V FT2 (UL) E67474

SPECIFICATIONS: CSA C22.2 No 49
UL 62