



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 14-41 3/C CU SJT PAPER 105\* 300V WHITE

**PRODUCT CODE:** 55-83-60-01

**JACKET:**

<b>NOMINAL OUTSIDE DIAMETER:</b>	.382"	in.
<b>NOMINAL WALL THICKNESS:</b>	.030"	in.
<b>COMPOUND:</b>	Polyvinyl Chloride	

**CONDUCTOR:**

<b>NUMBER OF CONDUCTORS:</b>	3	
<b>NOMINAL OUTSIDE DIAMETER:</b>	.136"	in.
<b>NOMINAL WALL THICKNESS:</b>	.030"	in.
<b>INSULATION COMPOUND:</b>	Polyvinyl Chloride	
<b>COPPER:</b>	14 AWG 41X.010" SBC	

**TEMPERATURE:**

105°C - max  
-20°C - min

**FILLERS:**

Paper filler

**PRINT:**

**INDENT**

**PRINT DESCRIPTION:** (UL) VW-1 E46194 (M) SJT 3/C 14 AWG (2.08mm<sup>2</sup>) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013