



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 14-41 3/C CU SJTOW N/F BLK 105°C 300V

**STOCK NUMBER:** 56-60-24-01

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .365" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 3  
**NOMINAL OUTSIDE DIAMETER:** .136" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 14 AWG 41X.010" SBC

**TEMPERATURE:** 105\*

**FILLERS:** N/A

**PRINT:** INDENT

**PRINT DESCRIPTION:** (UL) VW-1 E46194 (M) SJTOW 3/C 14 AWG (2.08mm<sup>2</sup>) 105°C DRY 60°C WATER RESISTANT  
300V (CSA) FT1, FT2 LL90458 (M) \*SCMW RoHS COMPLIANT"

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013