



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: SJTOW 14/3 41 SBC 105*

PRODUCT CODE: 56-45-52-01

JACKET:

NOMINAL OUTSIDE DIAMETER:	.380"	in.
NOMINAL WALL THICKNESS:	.030"	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	3	
NOMINAL OUTSIDE DIAMETER:	.136"	in.
NOMINAL WALL THICKNESS:	.030"	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	14 AWG 41X.010" SBC	

TEMPERATURE: 105C

FILLERS: Reinforced paperfiller

PRINT:

INDENT
(UL) VW-1 E46194 (M) SJTOW 3/C 14 AWG (2.08mm²) 105°C DRY 60°C WATER RESISTANT
300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194
CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013