



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 14-41 3/C CU SJTOW N/F BLK 105°C 300V

STOCK NUMBER: 56-60-24-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .365" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .136" in.
NOMINAL WALL THICKNESS: .030" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 14 AWG 41X.010" SBC

TEMPERATURE: 105*

FILLERS: N/A

PRINT: INDENT

PRINT DESCRIPTION: (UL) VW-1 E46194 (M) SJTOW 3/C 14 AWG (2.08mm²) 105°C DRY 60°C WATER RESISTANT
300V (CSA) FT1, FT2 LL90458 (M) *SCMW RoHS COMPLIANT"

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013