



Domtech Inc.
40 East Davis Street
Trenton, Ontario
Canada, K8V 6S4
Ph: 613-394-4884
Fax: 613-394-5372
Toll Free: 888-278-8258 (USA & Canada)
www.domtech.net

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

February 11, 2019

PART NUMBER: 1714691

DESCRIPTION: SJTOW 14(41B)/3 105C POLY-P YELLOW
.380",CC099(BLK-WHT-LGRN),SMOOTH,INDENT IW413 WR,VW-1,UL/CSA
30" PLY REEL-NR,1137M(3730FT)

CONDUCTOR: Stranded #14 awg 41x.0100" soft bare copper

INSULATION: PVC .030" minimum average thickness, diameter .136" +/- .002"

ASSEMBLY: Cabled with poly fillers and a 3.125" +/- .125" lay.
Paper separator applied between core and jacket.

COLOUR SEQUENCE: Black-White-Light Green (clockwise at top payoff end of spool)

JACKET: PVC .032" minimum average thickness.

OVERALL DIAMETER: .380" +/- .005"

TEMPERATURE: -40°C to 105°C

VOLTAGE: 300V

FLAME RATING: VW-1

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SJTOW 3/C 2,08mm² (14 AWG) 105°C DRY, 60°C WATER RESISTANT
300V VW-1 (UL) E67474

SPECIFICATIONS: CSA C22.2 No 49
UL62
RoHS Compliant

APPROVALS: CSA FILE NUMBER LL39965
UL FILE NUMBER E67474

