

BULK WIRE - FLEXIBLE CORD - PVC

TYPE SVT•UL•CSA•300V• 60°C-105°C*

Supplied on a 24" Non Returnable Reel

| CONDUCTOR NO. | CONDUCTOR | | NOMINALS (INCHES) | | | AMPS | SHIP WT. LBS./M FT. |
|---------------|-----------|-------|-------------------|--------|------|------|---------------------|
| | AWG. | STRD | INSUL | JACKET | O.D. | | |
| 2 | 18 | 41x34 | .015 | .030 | .235 | 10 | 30 |
| 3 | 18 | 41x34 | .015 | .030 | .245 | 10 | 38 |
| 4 | 18 | 41x34 | .015 | .030 | .255 | 7 | 44 |
| 2 | 17 | 52x34 | .015 | .030 | .245 | 11.5 | 36 |
| 3 | 17 | 52x34 | .015 | .030 | .260 | 11.5 | 46 |

Conductor: Fully annealed stranded bare copper.

Jacket: Thermoplastic (PVC) 300 volt ribbed or smooth

Note: Available with green or green/yellow ground.

Application: Used on floor polishers, sanders, vacuum cleaners, food mixers and office machines

Listed: UL-62 CSA-C22.2-49 RoHS Compliant

TYPE SJT•SJTO•SJTOW•UL•CSA•300V•60°C-105°C*

Supplied on a 24"- 30" Non Returnable Reel

| CONDUCTOR NO. | CONDUCTOR | | NOMINALS (INCHES) | | | AMPS | SHIP WT. LBS./M FT. |
|---------------|-----------|--------|-------------------|--------|------|------|---------------------|
| | AWG. | STRD | INSUL | JACKET | O.D. | | |
| 2 | 18 | 16x30 | .030 | .030 | .285 | 10 | 42 |
| 3 | 18 | 16x30 | .030 | .030 | .300 | 10 | 51 |
| 4 | 18 | 16x30 | .030 | .030 | .330 | 7 | 68 |
| 5 | 18 | 16x30 | .030 | .030 | .365 | 5.6 | 88 |
| 6 | 18 | 16x30 | .030 | .030 | .400 | 5.6 | 110 |
| 7 | 18 | 16x30 | .030 | .030 | .415 | 5.6 | 130 |
| 2 | 16 | 26x30 | .030 | .030 | .309 | 10 | 51 |
| 3 | 16 | 26x30 | .030 | .030 | .327 | 13 | 72 |
| 4 | 16 | 26x30 | .030 | .030 | .359 | 10 | 85 |
| 5 | 16 | 26x30 | .030 | .030 | .395 | 8 | 110 |
| 6 | 16 | 26x30 | .030 | .045 | .470 | 8 | 136 |
| 7 | 16 | 26x30 | .030 | .045 | .480 | 8 | 170 |
| 2 | 14 | 41x30 | .030 | .030 | .341 | 18 | 73 |
| 3 | 14 | 41x30 | .030 | .030 | .361 | 18 | 92 |
| 4 | 14 | 41x30 | .030 | .030 | .397 | 15 | 111 |
| 5 | 14 | 41x30 | .030 | .045 | .470 | 12 | 140 |
| 2 | 12 | 65x30 | .030 | .045 | .411 | 25 | 103 |
| 3 | 12 | 65x30 | .030 | .045 | .434 | 25 | 131 |
| 4 | 12 | 65x30 | .030 | .045 | .475 | 20 | 165 |
| 5 | 12 | 65x30 | .030 | .045 | .510 | 16 | 204 |
| 2 | 10 | 104x30 | .045 | .060 | .553 | 30 | 160 |
| 3 | 10 | 104x30 | .045 | .060 | .585 | 30 | 221 |

Conductor: Fully annealed stranded bare per ASTM B-174

Jacket: Polyvinyl Chloride (PVC)

Temperature: 105°C or 60°C (221°F or 140°F) to -40°C

Note: Available with green or green/yellow ground.

Applications: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

*Please contact U.S. Wire & Cable for availability.

