



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 16-26 2/C CU SJT 105\* 300V PAPER

**STOCK NUMBER:** 56-46-94-01

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .310" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 2  
**NOMINAL OUTSIDE DIAMETER:** .120" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 16 AWG 26 X .010" SBC

**TEMPERATURE:**

105°C - MAX  
-20°C - MIN

**FILLERS:**

Paperfiller

**PRINT:**

**INK**

(UL) VW-1 E46194 (M) SJT 2/C 16 AWG (1.31mm<sup>2</sup>) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - NOMA CABLETECH FILE NO. LL90458*

**SOUTHWIRE COMPANY**

3800 INDUSTRIAL PARKWAY  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013