



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: SJTOW 16/2 26SBC 105*

STOCK NUMBER: 56-58-63-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .310" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 2
NOMINAL OUTSIDE DIAMETER: .120" in.
NOMINAL WALL THICKNESS: .030" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 16 AWG 26X.010" SBC

TEMPERATURE: 105*

FILLERS: Reinforced paperfiller

PRINT:

PRINT DESCRIPTION: **INK**
(UL) VW-1 E47523 (M) SJTOW 2/C 16 AWG (1.31mm²) 105°C DRY 60°C WATER RESISTANT
300V (CSA) FT1,FT2 LL26332 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E47523

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL26332

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013