



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 18-41 CU SJTOW 105* Paper

STOCK NUMBER: 56-90-64-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .300" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 2
NOMINAL OUTSIDE DIAMETER: .109" in.
NOMINAL WALL THICKNESS: .030" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 18 AWG 41 X .0063" SBC

TEMPERATURE:

105°C - MAX
-40°C - MIN

FILLERS:

Paperfiller

PRINT:

INDENT

(UL) VW-1 E46194 (M) SJTOW 2/C 18 AWG (0.824mm²) 105°C DRY 60°C WATER RESISTANT
300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 INDUSTRIAL PARKWAY
MINERAL WELLS, TEXAS 76067

TEL (940) 328-1047

FAX (940) 328-1013