



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 18-41 3/C SJT PAPER BLACK 60°C 300V

STOCK NUMBER: 56-53-65-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .305" in.
NOMINAL WALL THICKNESS: .030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 3
NOMINAL OUTSIDE DIAMETER: .109" in.
NOMINAL WALL THICKNESS: .030" in.
INSULATION COMPOUND: Polyvinyl Chloride
COPPER: 18 AWG 41X.0063" SBC

TEMPERATURE: 60*

FILLERS: Reinforced paperfiller

PRINT:

INDENT

PRINT DESCRIPTION: (UL) VW-1 E46194(M) SJT 3/C 18AWG (0.82mm²) 60°C 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013