



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 18-16 3/C SJT 105\* 300V PAPER

**STOCK NUMBER:**

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** 0.330" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 3  
**CONDUCTOR COLORS:** Black, Black, Green  
**NOMINAL OUTSIDE DIAMETER:** .109" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 18 AWG 16X.010" SBC

**TEMPERATURE:** 105\*

**FILLERS:** Paperfiller

**PRINT:** **INDENT**

**PRINT DESCRIPTION:** (UL) VW-1 E46194 (M) SJT 3/C 18 AWG (0.824mm<sup>2</sup>) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

*UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194*

*CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458*

### **SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013