Domtech Inc.
40 East Davis Street,
Trenton, Ontario

Tel. (613) 394-4884 Tel. 1-800 278-8258 Fax (613) 394-0108

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

September 19, 2007

PART NUMBER: 1618386

DESCRIPTION: SJTW SHIELD-20(7T) 18(16B)/3 105C NF-T BLACK

.310",CC099(BLK-WHT-LGRN),SMOOTH,INDENT IW268,SHIELDED,

FT2,UL/CSA

30" PLY REEL-NR,1791M(5875FT)

CONDUCTOR: Stranded #18 awg 16x.010" soft bare copper

INSULATION: PVC .030" minimum average thickness

DIAMETER: .136" +/- .002"

ASSEMBLY: Cabled without fillers and a 2.125" +/- .125" lay.

Overall wrapped with aluminum/polyester shield, foil in, drain wire under shield

COLOUR SEQUENCE: Black-White-Light Green (clockwise at top of reel)

JACKET: Lead Free PVC .035" minimum average thickness.

DIAMETER: .310" +/- .005"

TEMPERATURE: -40 °C to 105 °C

VOLTAGE: 300

FLAME RATING: FT2

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SJTW 3/C 0,824mm2 (18 AWG) 105 °C 300V FT2

SHIELDED (UL) E67474

REGULATORY

APPROVALS: CSA FILE NUMBER LL39965

UL FILE NUMBER E67474