



# Southwire®

## SPECIFICATION SHEET

**PRODUCT DESCRIPTION:** 18-16 4/C CU SJTW PAPER 105\* 300V BLACK

**STOCK NUMBER:** 56-65-80-01

**JACKET:**

**NOMINAL OUTSIDE DIAMETER:** .350" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**COMPOUND:** Polyvinyl Chloride

**CONDUCTOR:**

**NUMBER OF CONDUCTORS:** 4  
**COLOR ROTATION CLOCKWISE:** Black, white, green-yellow, red  
**NOMINAL OUTSIDE DIAMETER:** .109" in.  
**NOMINAL WALL THICKNESS:** .030" in.  
**INSULATION COMPOUND:** Polyvinyl Chloride  
**COPPER:** 18 AWG 16X.010" SBC

**TEMPERATURE:**

105\* - MAX  
-40°C - MIN

**FILLERS:**

PAPER FILLER

**PACKAGE:**

30" PLYWOOD REEL

**PRINT:**

**INDENT**

(UL) VW-1 E46194 (M) SJTW 4/C 18 AWG (0.824mm<sup>2</sup>) 105°C DRY 60°C WATER RESISTANT  
300V (CSA) FT1,FT2 LL90458 (M)

**PRODUCT MANUFACTURED IN ACCORDANCE TO:**

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

**SOUTHWIRE COMPANY**

3800 Industrial Parkway  
MINERAL WELLS, TEXAS 76067  
TEL (940) 328-1047  
FAX (940) 328-1013