

SJTOW

105°C PVC Cord. 300 Volts. Flexible Copper Conductors. PVC Insulation and Jacket. Rated for Hard-Usage Service Cords. Rated UL VW-1 and CSA FT1, FT2 Flame Resistant.

CONSTRUCTION:

- Conductors:** Class K, Flexible bunch stranded bare copper per ASTM B3 and B174
Insulation: Polyvinyl Chloride (PVC)
Assembly: The insulated conductors are cabled together with fillers to form a round cable assembly. A tissue paper is helically applied over the assembly to facilitate overall jacket removal.
Jacket: Black, PVC

APPLICATIONS AND FEATURES:

Southwire Type SJTOW Flexible Cords are permitted for use as specified by Article 400 and related articles of the 2011 National Electric Code. Some typical applications for Type SJTOW Cord include, but are not limited to: Wiring for industrial machinery such as washing machines and other large appliances, heavy-duty portable tools, motors and temporary electrical

SPECIFICATIONS:

- ASTM B3, B174
- UL 62 - Type SJTOW
- CSA C22.2 No. 49 - Type SJTOW

SAMPLE PRINT LEGEND: (Indent)

(UL) VW-1 E46194 SJTOW 5/C 18 AWG (0.824mm²) 105°C DRY 60°C WATER RESISTANT 300V (CSA) FT1, FT2 LL90458 "RoHS COMPLIANT"

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (mils)	Jacket Thickness (mils)	Nominal OD (mils)	Nominal Weight (Lbs/Mft)	Color Code
583429XX	18	5	16	30	30	391	80	WHT/BLK/YEL/BLU/PNK

All dimensions are nominal and subject to normal manufacturing tolerances



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved

