

BULK WIRE - FLEXIBLE CORD - PVC

TYPE SVT•UL•CSA•300V• 60°C-105°C*

Supplied on a 24" Non Returnable Reel

CONDUCTOR NO.	CONDUCTOR		NOMINALS (INCHES)			AMPS	SHIP WT. LBS./M FT.
	AWG.	STRD	INSUL	JACKET	O.D.		
2	18	41x34	.015	.030	.235	10	30
3	18	41x34	.015	.030	.245	10	38
4	18	41x34	.015	.030	.255	7	44
2	17	52x34	.015	.030	.245	11.5	36
3	17	52x34	.015	.030	.260	11.5	46

Conductor: Fully annealed stranded bare copper.

Jacket: Thermoplastic (PVC) 300 volt ribbed or smooth

Note: Available with green or green/yellow ground.

Application: Used on floor polishers, sanders, vacuum cleaners, food mixers and office machines

Listed: UL-62 CSA-C22.2-49 RoHS Compliant

TYPE SJT•SJTO•SJTOW•UL•CSA•300V•60°C-105°C*

Supplied on a 24"- 30" Non Returnable Reel

CONDUCTOR NO.	CONDUCTOR		NOMINALS (INCHES)			AMPS	SHIP WT. LBS./M FT.
	AWG.	STRD	INSUL	JACKET	O.D.		
2	18	16x30	.030	.030	.285	10	42
3	18	16x30	.030	.030	.300	10	51
4	18	16x30	.030	.030	.330	7	68
5	18	16x30	.030	.030	.365	5.6	88
6	18	16x30	.030	.030	.400	5.6	110
7	18	16x30	.030	.030	.415	5.6	130
2	16	26x30	.030	.030	.309	10	51
3	16	26x30	.030	.030	.327	13	72
4	16	26x30	.030	.030	.359	10	85
5	16	26x30	.030	.030	.395	8	110
6	16	26x30	.030	.045	.470	8	136
7	16	26x30	.030	.045	.480	8	170
2	14	41x30	.030	.030	.341	18	73
3	14	41x30	.030	.030	.361	18	92
4	14	41x30	.030	.030	.397	15	111
5	14	41x30	.030	.045	.470	12	140
2	12	65x30	.030	.045	.411	25	103
3	12	65x30	.030	.045	.434	25	131
4	12	65x30	.030	.045	.475	20	165
5	12	65x30	.030	.045	.510	16	204
2	10	104x30	.045	.060	.553	30	160
3	10	104x30	.045	.060	.585	30	221

Conductor: Fully annealed stranded bare per ASTM B-174

Jacket: Polyvinyl Chloride (PVC)

Temperature: 105°C or 60°C (221°F or 140°F) to -40°C

Note: Available with green or green/yellow ground.

Applications: For use as portable power cord for power tools, motors, appliances and hospital equipment. Excellent resistance to water, acids, ozone and oils.

Listed: UL-62 CSA C22.2-49 OSHA RoHS Compliant

*Please contact U.S. Wire & Cable for availability.

