



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 18-16 6/C CU SJT 105°C 300V

STOCK NUMBER: N/A

JACKET:

NOMINAL OUTSIDE DIAMETER:	0.415"	in.
NOMINAL WALL THICKNESS:	0.030	in.
COMPOUND:	Polyvinyl Chloride	

CONDUCTOR:

NUMBER OF CONDUCTORS:	6	
CONDUCTOR COLORS:	BLACK,WHITE,RED,BLUE,BROWN,ORANG	
NOMINAL OUTSIDE DIAMETER:	0.109	in.
NOMINAL WALL THICKNESS:	0.030	in.
INSULATION COMPOUND:	Polyvinyl Chloride	
COPPER:	18 AWG 16X.010" SBC	

TEMPERATURE: 105°C - MAX
-20°C - MIN

FILLERS: Paperfiller

PRINT: **INDENT**
(UL) VW-1 E46194 (M) SJT 6/C 18 AWG (0.824mm²) 105°C 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013

၂E