

PVC/PVC - Type SJT

Portable Cord

UL: 105°C, 300V, VW-1

CSA: 105°C, 300V, FT2



IEWC Part Number	AWG	No. of Conductors	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx. Weight		Ampacity ⁰¹
				in	mm	in	mm	lbs/1k ft	kg/km	
SJT1802	18	2	16	0.030	0.8	0.287	7.3	40	60	10
SJT1803	18	3	16	0.030	0.8	0.305	7.7	53	79	10
SJT1805	18	5	16	0.030	0.8	0.391	9.9	80	119	7
SJT1602	16	2	26	0.030	0.8	0.310	7.9	49	73	13
SJT1603	16	3	26	0.030	0.8	0.330	8.4	64	95	13
SJT1402	14	2	41	0.030	0.8	0.340	8.6	78	116	18
SJT1403	14	3	41	0.030	0.8	0.365	9.3	90	134	18

⁰¹ SJT ampacities are for general use with ambient temperature @ 30°C per NEC Table 400.5

Notes

- Soft-annealed, bare copper conductor
- Polyvinyl chloride (PVC) insulation
- Polyvinyl chloride (PVC) jacket
- RoHS Compliant
- Standard jacket colors: black & white
- A variety of conductor color codes available

Alternative Constructions

- Coil cord

Available Certifications

CSA: FT1

Applications

For use in tool and appliance applications.
Rated for continuous use up to 105°C.