


# SKINTOP® MS-NPT BRUSH/MS-M BRUSH

Nickel-Plated Brass Strain Relief for EMC Applications with NPT & Metric Thread



The SKINTOP® MS-NPT/MS-M BRUSH provides centered, fixed strain relief with a liquid-tight and dust-proof seal, all in one step. Simply insert the cable, push the screen braid under the innovative EMC brush, tighten the cap, and the connection is made. The SKINTOP® MS-M BRUSH PLUS sizes offers extra large clamping ranges.

### Application Advantage

- Faster, easier, reliable screen contact
- Maximum assembly and adjustment possibilities
- 360° contact area allows for optimal low-resistance current return ground path

### Approvals: NPT Threads



### Approvals: Metric Threads



### Special Features

SKINTOP® sizes M75 x 1.5 to M110 x 2.0 feature the innovative double lamella gasket for easier assembling of cables with large diameters.

### Technical Data

<b>Material:</b> - Body: Nickel-plated brass - Brush: Brass - Insert: Polyamide - Bushing: Special elastomer - O-ring: Special elastomer	<b>Temperature Range:</b> - Static: -40°C to +100°C - Dynamic: -25°C to +100°C
<b>Locknuts:</b> Add SM-PE-M locknuts for metric glands, page 546	

Part Number	Thread Type & Size	øF Clamping Range (inches) (mm)		SW Wrenching Flats (inches)	C Overall Length (inches)	D Thread Length (inches)	Min ø above braiding (inches)	Standard Pack Size
<b>SKINTOP® MS-NPT BRUSH</b>								
53112037	NPT ¾"	0.354 - 0.669	9.0 - 17.0	1.142	1.694	0.591	0.236	10
53112047	NPT 1"	0.433 - 0.827	11.0 - 21.0	1.418	1.891	0.591	0.315	1
53112057	NPT 1¼"	0.748 - 1.103	19.0 - 28.0	1.773	2.265	0.669	0.394	1
53112067*	NPT 1½"	1.063 - 1.379	27.0 - 35.0	2.127	2.323	0.669	0.551	1
53112077*	NPT 2"	1.339 - 1.773	34.0 - 45.0	2.639	2.482	0.669	0.787	1
53112087*	NPT 2", plus	1.733 - 2.167	44.0 - 55.0	2.955	2.836	0.669	0.984	1
<b>SKINTOP® MS-M BRUSH</b>								
53112676	M25 x 1.5	0.354 - 0.669	9.0 - 17.0	1.142	1.418	0.315	0.236	10
53112677	M32 x 1.5	0.433 - 0.827	11.0 - 21.0	1.418	1.663	0.354	0.315	1
53112678	M40 x 1.5	0.748 - 1.103	19.0 - 28.0	1.773	2.344	0.354	0.394	1
53112679	M50 x 1.5	1.063 - 1.379	27.0 - 35.0	2.127	2.049	0.394	0.551	1
53112680	M63 x 1.5	1.339 - 1.773	34.0 - 45.0	2.639	2.415	0.591	0.788	1
53112681	M63 x 1.5, plus	1.733 - 2.167	44.0 - 55.0	2.955	2.719	0.591	0.985	1
53112501	M75 x 1.5	2.088 - 2.482	53.0 - 63.0	3.743	4.137	0.591	1.379	1
53112500	M75 x 1.5, plus	2.285 - 2.679	58.0 - 68.0	3.743	4.137	0.591	1.379	1
53112503	M90 x 2.0	2.600 - 3.073	66.0 - 78.0	4.531	5.339	0.788	1.773	1
53112505	M110 x 2.0	2.994 - 3.467	76.0 - 88.0	5.319	6.068	0.985	2.167	1
53112504	M110 x 2.0, plus	3.388 - 3.861	86.0 - 98.0	5.319	6.068	0.985	2.167	1

\* Available upon request

Photographs are not to scale and are not true representations of the products in question.

For current information go to our website. If not otherwise specified, all values relating to the product are nominal values.