



US North Central
 5001 S. Towne Drive
 New Berlin, WI 53151
 800-344-2323
 www.IEWC.COM

Issue Date: 8/25/2014
 Issue: 1
 Reference: IQ14320

Construction

Description:	1PR 20 10/30TC PE BLK & RED + 1/C 20 7/28 TC PVC O/A PVC JKT GRAY	Diam. (In)
Component:		
Conductor 1:	20 7/28 TC to ASTM B 33-74	0.038
Insulation:	Petro GA-808093(LDPE) 0.016 WALL	0.070
Color Code	Natural x 1	
Conductor2:	20 10/30 TC	
Insulation:	Petro GA-808093(LDPE) 0.015 WALL	0.066"
Color Code	RED , BLACK	
Pair Assembly	20 10/30 TC Red and Black twisted to form one unshielded twisted pair.	0.132
Cable Assembly	Cable Unshielded 20 10/30 The Colors: <i>Red & Black</i> Pair with The Single Conductor 20 10/30 The Color: <i>Natural</i> to Form one Complete cable. (<i>The Completed Cable nor the twisted pair Have A Shield or Drain Wire</i>)	0.150
Jacket:	Sylvin 6168-80N 0.028 WALL	0.206
Jacket Color:	GRAY	
Print:	E174416 RU AWM STYLE 2093 80C 300V --- LL109360 CSA AWM I/II A/B 300V 80C FT-1	
Specifications:	UL 2093 300V 80°C RoHS CSA I/II A/B FT-1	
Environmental Compliance	<p>EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.</p> <p>REACH Regulation (EC 1907/2006): This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.</p> <p>California Prop 65: The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.</p>	

W T Shultz
 10/1/14