



## SayFlex Braided Monofilament Sleeving

SayFlex is a braided monofilament Sleeving of polyethylene terephthalate (PET)

- lightweight
- inert to most chemicals
- resistant to fungus
- excellent abrasion
- cut-through resistance

### SayFlex Features:

- Rated for continuous service from -70°C through 125°C. and will tolerate short-term exposure up to 230°C.
- Shapes to a snug fit producing a compact bundle with a smooth resilient cover, which prevents snagging during installation in cabinets and equipment.
- Naturally slick allowing it to slide easily and quickly over end fittings and connectors, reducing labor cost. Bundled elements move freely within the sleeve reducing strain.
- Adds minimal weight, bulk and cost to wire harnesses.
- Stretches and contracts to accommodate irregular shapes and sizes. A single sleeve size can stretch to encase bundles with diameters up to three times its own I.D.
- Can be flexed repeatedly without losing its physical properties. Its open braid construction affords ventilation, preventing trapping of heat or moisture.
- Resists chafing, abrasion, cut-through, flexure-fatigue, and heat degradation.

### SayFlex - Physical Properties

PROPERTY	ASTM METHOD	TYPICAL VALUES
Strand Diameter	----	.010"
Tensile Strength, PSI	D-876	100,000
Elongation, %	D-876	20
Melt Temperature, °C	D-2217	260

### SayFlex Availability:

Available in a wide range of diameters ranging from 1/8" through 3 3/4" O.D. SayFlex is available in black, white, and clear. A range of other colors, including fluorescent, is also available subject to availability and minimum order quantities.

Made in the USA 

\* The above data is informational only and should not be used for specification purposes\*



**SayFlex**

**SAYFLEX PUTUPS**

<b>Saylor PN#</b>	<b>Breyden PN#</b>	<b>Size I.D.</b>	<b>Expandable Capabilities</b>	<b>LBS/1000'</b>	<b>Standard Spool</b>
<b>SF 1/8"</b>	P22201	1/8"	3/32" - 1/8"	1.8	1000 ft.
<b>SF 1/4"</b>	P22202	1/4"	1/8" - 3/8"	2.6	1000 ft.
<b>SF 3/8"</b>	P22203	3/8"	3/16" - 5/8"	5.7	500 ft.
<b>SF 1/2"</b>	P22204	1/2"	1/4" - 3/4"	7.4	500 ft.
<b>SF 3/4"</b>	P22205	3/4"	1/2" - 1 1/4"	12.5	250 ft.
<b>SF 1"</b>	P22206	1"	5/8" - 1 5/8"	14.2	250 ft.
<b>SF 1 1/4"</b>	P22207	1 1/4"	3/4" - 1 1/2"	15.8	250 ft.
<b>SF 1 1/2"</b>	P22208	1 1/2"	1" - 2 1/2"	19.6	250 ft.
<b>SF 1 3/4"</b>	P22209	1 3/4"	1 1/4" - 2 3/4"	26.3	200 ft.
<b>SF 2"</b>	P22210	2"	1 1/2" - 3"	34.2	100 ft.
<b>SF 2 1/2"</b>	P22211	2 1/2"	1 3/4" - 3 1/2"	37.5	100 ft.