



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

Royal[®] 600V SOOW

Construction Parameters:

CONDUCTOR: 8 AWG - 2 AWG Class K stranded bare copper per ASTM B-174
INSULATION: EPDM
JACKET: CPE
COLOR: Black (Other colors available upon request)
PRINT LEGEND: CCI ROYAL XX AWG (X.XXmm²) X/C SOOW 600V -40C TO 90C
INDENT LEGEND: P-07-KA070018-1-MSHA

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 90°C
FEATURES: Ozone, Sunlight, Chemical & Oil Resistant, Water, and flame-retardant Jacket

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

INDUSTRY APPROVALS:

- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'	Color Code
				Inches	mm	Inches	mm	Lb./kft.	kg/km			
822220	8	2	133/0.0106	0.050	1.27	0.632	16.05	274	408	40	0.72	Black, White
822320	8	3	133/0.0106	0.050	1.27	0.645	16.38	302	449	40	0.72	Black, White, Green
822420	8	4	133/0.0106	0.050	1.27	0.716	18.19	443	659	35	0.72	Black, White, Red, Green
822470	8	5	133/0.0106	0.050	1.27	0.834	21.18	506	753	28	0.72	Black, White, Red, Orange, Green
822221	6	2	133/0.0141	0.050	1.27	0.721	18.31	351	522	55	0.40	Black, White
822321	6	3	133/0.0141	0.050	1.27	0.726	18.44	468	696	55	0.40	Black, White, Green
822421	6	4	133/0.0141	0.050	1.27	0.803	20.40	626	932	45	0.40	Black, White, Red, Green
822521	6	5	133/0.0141	0.050	1.27	0.937	23.80	780	1161	36	0.40	Black, White, Red, Orange, Green
822222	4	2	133/0.0171	0.050	1.27	0.852	21.64	478	711	70	0.40	Black, White
822322	4	3	133/0.0171	0.050	1.27	0.824	20.93	664	988	70	0.27	Black, White, Green
822422	4	4	133/0.0171	0.050	1.27	0.950	24.13	869	1293	60	0.27	Black, White, Red, Green
822522	4	5	133/0.0171	0.050	1.27	1.027	26.09	1032	1536	48	0.27	Black, White, Red, Orange, Green
822223	2	2	133/0.0220	0.050	1.27	1.084	27.53	712	1060	95	0.16	Black, White
822323	2	3	133/0.0220	0.050	1.27	0.979	24.87	1062	1580	95	0.16	Black, White, Green
822423	2	4	133/0.0220	0.050	1.27	1.086	27.58	1286	1914	80	0.16	Black, White, Red, Green
822523	2	5	133/0.0220	0.050	1.27	1.323	33.60	1606	2390	64	0.16	Black, White, Red, Orange, Green

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.
 * Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2002/95/EC (RoHS)
 The customer will accept all factory lengths and +/- 10 percent of total order requested.
 The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: October 9, 2013