



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
 Waukegan, IL 60085  
 Toll-Free (800) 323-9355  
 Fax: (847) 689-1192

## Royal<sup>®</sup> 600V SOOW

### Construction Parameters:

**CONDUCTOR:** 8 AWG - 2 AWG Class K stranded bare copper per ASTM B-174  
**INSULATION:** EPDM  
**JACKET:** CPE  
**COLOR:** Black (Other colors available upon request)  
**PRINT LEGEND:** SOUTHWIRE<sup>®</sup> ROYAL<sup>®</sup> CORD XX/C XX AWG (XXmm2) SOOW 600V -40C TO 90C

**IDENT LEGEND:** P-07-KA070018-1-MSHA

### PHYSICAL PROPERTIES:

**TEMPERATURE RANGE:** -40°C to 90°C  
**FEATURES:** Ozone, Sunlight, Chemical & Oil Resistant, Water, and flame-retardant Jacket

### ELECTRICAL PROPERTIES:

**VOLTAGE RATING:** 600V rms, Max

### INDUSTRY APPROVALS:

- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'	Color Code	
			Inches	mm	Inches	mm	Lb./kft.	kg/km				
569972	8	2	133/0.0106	0.050	1.27	0.632	16.05	274	408	40	0.72	Black, White
558088	8	3	133/0.0106	0.050	1.27	0.645	16.38	302	449	40	0.72	Black, White, Green
558093	8	4	133/0.0106	0.050	1.27	0.710	18.03	443	659	35	0.72	Black, White, Red, Green
558105	8	5	133/0.0106	0.050	1.27	0.834	21.18	506	753	28	0.72	Black, White, Red, Green, Orange
569973	6	2	133/0.0141	0.050	1.27	0.721	18.31	351	522	55	0.40	Black, White
558092	6	3	133/0.0141	0.050	1.27	0.726	18.44	468	696	55	0.40	Black, White, Green
558091	6	4	133/0.0141	0.050	1.27	0.803	20.40	626	932	45	0.40	Black, White, Red, Green
558161	6	5	133/0.0141	0.055	1.40	0.937	23.80	780	1161	36	0.40	Black, White, Red, Green, Orange
	4	2	133/0.0171	0.060	1.52	0.672	17.07	478	711	70	0.40	Black, White
558137	4	3	133/0.0171	0.050	1.27	0.824	20.93	664	988	70	0.27	Black, White, Green
558090	4	4	133/0.0171	0.050	1.27	0.950	24.13	869	1293	60	0.27	Black, White, Red, Green
569975	4	5	133/0.0171	0.050	1.27	1.027	26.09	1032	1536	48	0.27	Black, White, Red, Green, Orange
558136	2	3	133/0.0220	0.050	1.27	0.979	24.87	1062	1580	95	0.16	Black, White, Green
558089	2	4	133/0.0220	0.050	1.27	1.086	27.58	1286	1914	80	0.16	Black, White, Red, Green
569976	2	5	133/0.0220	0.050	1.27	1.323	33.60	1606	2390	64	0.16	Black, White, Red, Green, Orange

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

\* Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2011/65/EU (RoHS-2)  
 The customer will accept all factory lengths and +/- 10 percent of total order requested.  
 The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: February 16, 2015