



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

Royal® 600V SOOW

Construction Parameters:

CONDUCTOR: 16 AWG Class K stranded bare copper per ASTM B-174
INSULATION: EPDM
JACKET: CPE
COLOR: Black (Other colors available upon request)
PRINT LEGEND: SOUTHWIRE® ROYAL® (5 CROWN LOGO) CORD 3/C 16 AWG (1.31mm²) SOOW E46194 (UL) 600V -40C TO 90C -- CSA LL90458 SOOW 600V -40C TO 90C FT2 WATER RESISTANT

INDENT LEGEND: P-07-KA070018-1-MSHA

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 90°C
WATER RESISTANT: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

Industry Approvals:

- o UL Standard 62
- o NEC Article 501.140 Class I Div. 2
- o NEC Article 400
- o CSA C22.2 No. 49
- o Passes CSA FT2 Flame Test
- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Norm. DCR Ω/1M'	Nom. Lay Length in.	Color Code	
			Inches	mm	Inches	mm	Lb./kft.	kg/km					
576878	16	3	26/30	0.030	0.76	0.395	10.03	94	140	13	4.05	2.00	Black Red Lt Blue

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.
 *Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2011/65/EU (RoHS-2)
 The customer will accept all factory lengths and +/- 10 percent of total order requested.
 The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented herein is, to the best of our knowledge, true and accurate. Once customers or their agents confirm a purchase order, Southwire's product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: November 12, 2014