


# Super Vu-Tron® Multi-Conductor Type S00W

90°C, 600 Volt, UL/CSA Portable Cord



### TYPE S00W - 600 VOLT - UL/CSA

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOMINAL INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS†	APPROX. NET WT. LBS/M <sup>(S)</sup>
				INCHES	mm	INCHES	mm		
09805	5	18	16/30	0.030	0.76	0.465	11.81	5.6	141
09806	6	18	16/30	0.030	0.76	0.495	12.57	5.6	152
09807	7	18	16/30	0.030	0.76	0.520	13.21	5.6	172
09808	8	18	16/30	0.030	0.76	0.530	13.46	4.9	177
09810	10	18	16/30	0.030	0.76	0.595	15.11	4.9	225
09812	12	18	16/30	0.030	0.76	0.600	15.24	3.5	240
09814	14	18	16/30	0.030	0.76	0.630	16.00	3.5	265
09816	16	18	16/30	0.030	0.76	0.700	17.78	3.5	310
09818*	18	18	16/30	0.030	0.76	0.760	19.30	3.5	345
09820	20	18	16/30	0.030	0.76	0.795	20.19	3.5	382
09822*	22	18	16/30	0.030	0.76	0.805	20.45	3.1	400
09824	24	18	16/30	0.030	0.76	0.850	21.59	3.1	451
09827*	27	18	16/30	0.030	0.76	0.865	21.97	3.1	475
09830*	30	18	16/30	0.030	0.76	0.915	23.24	3.1	533
09605	5	16	26/30	0.030	0.76	0.495	12.57	8.0	167
09606	6	16	26/30	0.030	0.76	0.520	13.21	8.0	182
09607	7	16	26/30	0.030	0.76	0.540	13.72	8.0	194
09608	8	16	26/30	0.030	0.76	0.575	14.61	7.0	218
09609	9	16	26/30	0.030	0.76	0.600	15.24	7.0	243
09610	10	16	26/30	0.030	0.76	0.620	15.75	5.0	255
09612	12	16	26/30	0.030	0.76	0.660	16.76	5.0	296
09614	14	16	26/30	0.030	0.76	0.730	18.54	5.0	352
09616	16	16	26/30	0.030	0.76	0.740	18.80	5.0	383
09618*	18	16	26/30	0.030	0.76	0.770	19.56	5.0	417
09620	20	16	26/30	0.030	0.76	0.810	20.57	5.0	457
09622*	22	16	26/30	0.030	0.76	0.900	22.86	4.5	510
09624	24	16	26/30	0.030	0.76	0.925	23.50	4.5	563
09626*	26	16	26/30	0.030	0.76	0.965	24.51	4.5	611
09630	30	16	26/30	0.030	0.76	1.010	25.65	4.5	767

† Values shown are for current-carrying conductors. A grounding conductor, or one which carries only the unbalance current from other conductors, is NOT counted in determining current carrying capacity. Ampacities based on NEC Table 400.5(A)(1).

\* Non-stock item; minimum quantity purchase required.

<sup>(S)</sup>Actual shipping weight may vary.

### COLOR CODE CHART

NO. OF COND.	COLOR	TRACER	NO. OF COND.	COLOR	TRACER	NO. OF COND.	COLOR	TRACER
1	Black	—	8	Red	Black	15	Blue	White
2	White	—	9	Green	Black	16	Black	Red
3	Red	—	10	Orange	Black	17	White	Red
4	Green	—	11	Blue	Black	18	Orange	Red
5	Orange	—	12	Black	White	19	Blue	Red
6	Blue	—	13	Red	White	20	Red	Green
7	White	Black	14	Green	White	21	Orange	Green

Note: Colors repeat after 21 conductors.

### Product Construction:

#### Conductors:

- 18 and 16 AWG fully annealed stranded bare copper

#### Insulation:

- Premium-grade, color-coded 90°C EPDM
- Color code: See chart below

#### Jacket:

- Super Vu-Tron® 90°C, black
- Temperature range: -40°C to +90°C

#### Jacket Marking:

- CAROL SUPER VU-TRON® (SIZE) (mm<sup>2</sup>) 90°C (UL) WATER RESISTANT SOOW CSA (-40°C) FT2 P-7K-123033 MSHA 600 VOLT ROHS MADE IN USA (TRU-MARK SEQUENTIAL FOOTAGE)

### Applications:

- Control circuits
- Tools
- Heavy industrial, processing and construction equipment

### Features:

- Extra-flexible stranding
- Abrasion-resistant
- Resists oils and solvents
- Flame-resistant
- Ozone-resistant
- 90°C rated conductors and jacket
- Water-resistant\*
- UL Listed and CSA Certified for indoor and outdoor use
- Ozone-, sunlight (UV)- and weather-resistant
- TRU-Mark® sequential footage marking

### Industry Approvals:

- UL Flexible Cord - UL 62
- CSA Flexible Cord - C22.2-49
- MSHA Approved
- RoHS Compliant

### Packaging:

- 5- through 8-conductor available on 250' (76.2 m), 500' (152.4 m), and 1000' (304.8 m) reels
- 9+ cond. available on long-length reels
- Other put-ups available on special order

\* Suitable for immersion in water if properly sealed and terminated.

