



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: SPT-3 12/3 65 SBC (DD)

STOCK NUMBER: 55-68-38-01

JACKET:

NOMINAL OUTSIDE DIAMETER: .285"(Minor) - .600"(Major) in.
NOMINAL WALL THICKNESS: .094" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 1
NOMINAL OUTSIDE DIAMETER: .127" in.
NOMINAL WALL THICKNESS: .015" in.
INSULATION COMPOUND: Polyvinyl Chloride - ground conductor
COPPER: 12 AWG 65X.010" SBC

TEMPERATURE: 105* - max
-20* - min

INSULATION HARDNESS: NOMINAL - 86

FILLERS: N/A

PRINT: **INDENT**

PRINT DESCRIPTION: (UL) VW-1 E46194 (M) SPT-3 3/C 12 AWG (3.31mm²) 105°C GREEN CONDUCTOR FOR GROUNDING ONLY 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013