



SPECIFICATION SHEET

PRODUCT DESCRIPTION: SPT-3 12/3 65 SBC (DD)

PRODUCT CODE: 702425

JACKET:

NOMINAL OUTSIDE DIAMETER: .285"(Minor) - .587"(Major) in.
NOMINAL WALL THICKNESS: .094" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 1
NOMINAL OUTSIDE DIAMETER: .127" in.
NOMINAL WALL THICKNESS: .015" in.
INSULATION COMPOUND: Polyvinyl Chloride - ground conductor
COPPER: 12 AWG 65X.010" SBC

TEMPERATURE: 105*

FILLERS: N/A

PRINT: INDENT

PRINT DESCRIPTION: (UL) VW-1 E47523 (M) SPT-3 3/C 12 AWG (3.31mm²) 60°C GREEN CONDUCTOR FOR GROUNDING ONLY 300V (CSA) FT1,FT2 LL26332 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - CABLETECH GLOBAL FILE NO. E47523

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - CABLETECH GLOBAL FILE NO. LL26332

CABLETECH GLOBAL

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013

Date created: 9/30/08