## **PRODUCT SPECIFICATION**

DATE	REV	<b>ECN</b>	DESCRIPTION
7/30/2015	С		UPDATED E NUMBER

Tolerance +/-

0.010

RIPPED WALL MIN

0.040

**NOM WALL** 

MIN WALL

0.060

0.054

0.427

**MAJOR:** 

0.005

0.054

COND. TO COND. MIN:

*MINOR:* 0.189

*Tolerance* +/-

CF Parent Number: FST010-C

Description: 16/3 26/30 BC SPT-3 105C Green Ground

Style: UL: SPT-3, CSA: SPT-3

**Stranding:** 26/30 BC LHL, OD = 0.056"

Ground: 16 26/30 BC LHL SPT Ground LGN OD 0.088"

**Insulation:** PVC

Print Legend: 16 AWG (1.31mm2) 3/C E46194 (PLANT ID CODE) (UL) SPT-3 105C 300V VW-1 - - - 156205 CSA SPT-3 105C 300V FT-1 Green

conductor for grounding only

Voltage: 300V

**Temperature:** 105C

Notes: 1. ONE CONDUCTOR FULLY RIBBED.

2. INDENT PRINT ON SMOOTH CONDUCTOR.

This product complies with European Directive 2011/65/EU (RoHS-2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

## **Customer Approval:**

Approved By:	
Title:	Company Name:



Southwire'

Copperfield

1115 W. North Street Bremen, IN 46506 Phone: 574-546-5115

Fax: 574-546-5995