



Domtech Inc.
40 East Davis Street, Tel. (613) 394-4884
Trenton, Ontario Tel. 1-800 278-8258
Canada K8V 6S4 Fax (613) 394-0108

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

January 17, 2012

PART NUMBER: 2916510

DESCRIPTION: SPT-3 16(26B)/3 105C GREY
.194"X.435",INDENT,IW015,VW-1,UL/CSA
30" HDPLY REEL-R,1524M(5000FT)

CONDUCTORS: Stranded #16 awg 26x.0100" soft bare copper

GROUND WIRE: Stranded #16 awg 26x.0100" soft bare copper
PVC .015" minimum average thickness, .091" +/- .002"

ASSEMBLY: Parallel, flat, two conductors integral, non-integral green ground
wire in center

OVERALL INSULATION: PVC .060" minimum average thickness
DIAMETER: .194" +/- .005" x .435" +/- .008"

TEMPERATURE: 105°C

VOLTAGE: 300

FLAME RATING: VW-1

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SPT-3 3/C 1.31mm² (16 AWG)105°C 300V
VW-1 GREEN CONDUCTOR FOR GROUNDING ONLY (UL) E67474

REGULATORY

APPROVALS: CSA FILE NUMBER LL39965
UL FILE NUMBER E67474
RoHS Compliant