

Part Number: X336476

Revision: 7/15/2014

**2C 18AWG PVC PARALLAL**

**SPECIALTY CORD**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#18 AWG (16/30) Tinned Copper with Overcoat	.048" Nom
Cable Assembly:	2 Conductors pulled in parallel	
Insulation:	.033" Wall, Polyvinyl Chloride (PVC)	.228" x .115" Nom
Sequential Footage:	None	
Packaging Note:	Level Traverse Required - No kinks or twists allowed.	
Print Legend:	<b>ISOTEC (R) BRAND - 18 AWG E11368-8 C(UL)US SPT-1 OR AWM 2300</b>	

**B. INDUSTRY APPROVALS**

National Electric Code	Article 400
UL Standard 62	Type SPT-1
UL Standard 758	AWM Style 2300

**C. ELECTRICAL PROPERTIES**

Temperature:	-20°C to +105°C
Suggested Working Voltage:	300 Vrms (Max)
Conductor DCR:	7.20 Ohms/1000ft @ 20°C (Max)
Capacitance (Cond-Cond):	24.0 pF/ft @ 1kHz (Nom)

**D. COLOR CODE**

Color per order

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_

Date: \_\_\_\_\_