

Electrical Wire and Cable

Domtech Inc. 40 East Davis Street, Trenton, Ontario Canada K8V 6S4

Tel. (613) 394-4884 Tel. 1-800 278-8258 Fax (613) 394-0108

FOR REFERENCE ONLY, THIS IS NOT A CONTROLLED DOCUMENT

PRODUCT SPECIFICATION

January 31, 2012

PART NUMBER: 2818003

DESCRIPTION: SPT-2 18(41B)/3 105C BLACK

.150"X.347",INDENT IW292,VW-1,UL/CSA

24" PLY REEL-NR,1524M(5000FT)

CONDUCTOR: Stranded #18 awg 41x.0063" soft bare copper

GROUNDWIRE: PVC .015" minimum average thickness, .079" +/- .002

OVERALL INSULATION: PVC .045" minimum average thickness

DIAMETER: .150" +/- .005" x .347" +/- .006"

ASSEMBLY: Parallel, flat, integral with insulated groundwire in center.

Print on ribbed side of conductor.

TEMPERATURE: 105°C

VOLTAGE: 300

FLAME RATING: VW-1

PRINT TYPE: Indent

PRINT LEGEND: CSA LL39965 SPT-2 3/C 0,824mm2 (18 AWG)105°C 300V VW-1

GREEN CONDUCTOR FOR GROUNDING ONLY (UL) E67474

REGULATORY

APPROVALS: CSA FILE NUMBER LL39965

UL FILE NUMBER E67474

RoHS Compliant