



Southwire®

SPECIFICATION SHEET

PRODUCT DESCRIPTION: 18-41 3/C SPT-1 105* 300V

STOCK NUMBER: 56-45-90-01

JACKET:

NOMINAL OUTSIDE DIAMETER: 0.111"(Minor) - 0.275"(Major) in.
NOMINAL WALL THICKNESS: 0.030" in.
COMPOUND: Polyvinyl Chloride

CONDUCTOR:

NUMBER OF CONDUCTORS: 1
NOMINAL OUTSIDE DIAMETER: .082" in.
NOMINAL WALL THICKNESS: .016" in.
INSULATION COMPOUND: Polyvinyl Chloride(Ground Conductor Only)-Grn
COPPER: 18 AWG 41X.0063" SBC

TEMPERATURE: 105°C

FILLERS: N/A

PRINT:

INDENT

(UL) VW-1 E46194 (M) SPT-1 3/C 18 AWG (0.824mm²) 105°C GREEN CONDUCTOR FOR GROUNDING ONLY 300V (CSA) FT1,FT2 LL90458 (M)

PRODUCT MANUFACTURED IN ACCORDANCE TO:

UL STANDARD NO. 62 FLEXIBLE CORDS AND FIXTURE WIRES - FILE NO. E46194

CSA STANDARD C22.2 NO. 49 FLEXIBLE CORDS - FILE NO. LL90458

SOUTHWIRE COMPANY

3800 Industrial Parkway
MINERAL WELLS, TEXAS 76067
TEL (940) 328-1047
FAX (940) 328-1013