

1. CONDUCTOR (4):

- 1.1 Size and Material: 16 7/.0192" AWG tin-plated copper wire.
- 1.2 O.D.: .058" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 *Print on the insulation: as per UL and CSA Standards.*
- 2.3 O.D.: .118" nom.
- 2.4 Color code: black, red, green, white.
- 2.5 Talc powder applied on the insulation.

3. CABLING:

- 3.1 The four wires are twisted together.
- 3.2 Binber: spiral-wrapped polyester tape.
- 3.3 O.D.: .286" nom.

4. JACKET:

- 4.1 Extruded silicone rubber.
- 4.2 O.D.: .376" nom.
- 4.3 Color: black.
- 4.4 Talc powder applied on the jacket.

5. PERFORMANCE:

- 5.1 Voltage rating: 600 VAC R.M.S.
- 5.2 Temperature rating: 200°C






6. REFERENCE (INNER WIRES ONLY):

- 6.1 *UL subject 758 (AWM), Style 3530.*
- 6.2 *CSA standard C22.2 No.210.2-M90 (AWM), Class I Group A.*

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: 		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com</p>			
1062								Date: January 22, 2004					
								Verified: 		Description: 4(XSR30Z167/0192)MTRSR 0-2-5-9/0			
								Date: January 22, 2004					
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>	Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F02735-S