

1. CONDUCTOR (2):

- 1.1 Size and Material: 20 7/.0121" AWG nickel-plated copper wire.
- 1.2 O.D.: .036" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .096" nom.
- 2.4 Color code: black, white.
- 2.5 Talc powder applied on the insulation.

CUSTOMER APPROVAL

Sign: _____
Date: _____

3. CABLING:

- 3.1 The two wires are twisted together.
- 3.2 Binder: spiral-wrapped polyester tape
- 3.3 O.D.: .192" nom.

4. JACKET:




- 4.1 Extruded silicone rubber.
- 4.2 O.D.: .284" nom.
- 4.3 Color: black.
- 4.4 Talc powder applied on the jacket.

5. PERFORMANCE:

- 5.1 Voltage rating: 600 VAC R.M.S.
- 5.2 Temperature rating: 200°C

6. REFERENCES:

- 6.1 UL Subject 758 (AWM), Style 3530 (for inners only).
- 6.2 CSA Standard C22.2 No.210 (AWM), Class I Group A (for inners only).

Engineering Change Notice No.								 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i>		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>				
1062	1512								Date: January 25, 2008						
									Verified: <i>Carole L...</i>						
									Date: January 25, 2008		Description: 2(XSR30N207/0121)MTSR 0-9/0				
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									 A member of The Marmon Group of companies		Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F02736-S