

SR255X0HIHSUVH1

Article Number: 115-42100

Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 500/plain pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SR255X0HIHSUVH1

Type SR255X

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Special design offers a release feature for quick and easy access to wire bundles.
- Head design provides high tensile strength with very low insertion force even after repeated use.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Short Description Releasable Cable Tie, 14.6" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 500/plain pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1115.0 N

Length L (Imperial) 14.6 "

Length L (Metric) 370.0 mm

Width W (Imperial) 0.5 "

Width W (Metric) 12.6 mm

Bundle Diameter Min. (Imperial) 0.51 "

Bundle Diameter Min. (Metric) 13.0 mm

Bundle Diameter Max. (Imperial) 3.9 "

Bundle Diameter Max. (Metric) 100.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes