			DATE	REV	ECN	DESCRIPTION
PRODUCT	SPECIFICATION		7/29/2009	D	20977	SPECIFICATION UPDATED
Parent Number:	F08025-					
Description:	8 54/25 TC AWM 3125 SEW-2 Braided	DIAMETER: <u>O</u>	<u>).275</u>			
	Silicone	TOLERANCE \pm : O	.002			
					/ 688	9
<u>Stranding:</u>	<u>54/25 TC LHL</u>			_		MIN AVG WALL: 0.060
<u>Style:</u>	UL: AWM 3125 CSA: SEW-2					MINIMUM WALL: 0.054
<u>Insulation:</u>	Braided Silicone					
Print Legend: 8 AWG (8.367mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3125 200C 600V 156205 CSA SEW-2 200C 600V FT1						
-						
Voltage	6001/					
<u>Voltage:</u> <u>600V</u>						
Temperature: 200C						
N. (
<u>Notes:</u>	 Diameter shown is OD under braid. The OD over the braid is approximately 0.300". 					
The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational						
purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of						
information contained		6		·	(# 3)	Southwire'
This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclose to any party without written consent of Southwire Company, LLC.				ISCIOSED	Sec. 1	
Customer Appro	oval:				1	Copperfield
	t Nbr(s):					1 1
Approved By:_	Date:					5 W. North Street men, IN 46506
Title:_	CompanyCOMPANY	y Name:		<u></u>		men, 11v 40500 ne: 1-574-546-5115