PRODUCT SPECIFICATION

DATEREVECNDESCRIPTION4/10/2007B16655SPECIFICATION UPDATED

CF Parent Number: F12046-


Description: 12 65/30 TC AWM 3070 SEWF-2 Braided

Silicone

* **DIAMETER**: 0.155

TOLERANCE ± : 0.002

* Diameter shown is under braid.



→ *NOMINAL WALL:* <u>0.030</u>

MINIMUM WALL: 0.027

Stranding: 65/30 TC LHL

Style: UL: AWM 3070 CSA: SEWF-2

Insulation: Braided Silicone

Print Legend: 12 AWG (3.31mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 3070 150C 600V --- 156205 CSA SEWF-2 150C 600V FT1

Voltage: 600V

Temperature: 150C

Notes: 1. Diameter shown is OD under braid.

2. The OD over the braid is approximately 0.166".

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Approved By:______Date:_____

Title:______Company Name:_____

Southwire*

Copperfield

1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115