PRODUCT SPECIFICATION

DESCRIPTION DATE REV **ECN** 7/2/2010 #13004 SPECIFICATION UPDATED

CF Parent Number: F14052-

Description: 14 7/.0242 TC AWM 3071/3231 SF-2 SEW-

2 Braided Silicone

* *DIAMETER*: 0.132

 $TOLERANCE \pm : 0.003$

* Diameter shown is under braid.

→ *NOMINAL WALL*: 0.030

MINIMUM WALL: 0.027

Stranding: 7/.0242 TC LHL

Insulation: Braided Silicone

<u>Print Legend:</u> 14 AWG (2.08mm2) E30071 (PLANT ID CODE) (UL) TYPE SF-2 OR AWM 3071/3231 200C 600V -- 156205 CSA SEW-2 200C 600V FT1

Voltage: 600V

Temperature: 200C

Notes: 1. Diameter shown is OD under braid.

2. OD over the braid is approximately 0.143"

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without written consent of Southwire Company, LLC.

Customer Approval:

Approved By: _______ Date:_____ Title:_____Company Name:_____

Southwire' 1115 W. North Street Bremen, IN 46506

Phone: 1-574-546-5115