

1. CONDUCTOR:

- 1.1 Size and Material: 14 7/.0242" AWG tin-plated copper wire.
- 1.2 O.D.: .072" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Print on insulation: as per UL and CSA Standards.
- 2.3 Covering: braided fiberglass yarn impregnated with a saturant to minimize fraying.
- 2.4 O.D.: .147" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:






- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C

4. REFERENCE:

- 4.1 UL Standard 66 (Fixture Wire), Type SF-2.
- 4.2 CSA Standard C22.2 No. 127-99 (Equipment and Lead Wires), Type SEW-2.

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.							 This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: 		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourintl.com			
								Date: July 15, 2004					Description: XSR30Z147/0242GB-X
								Verified: 		Code Ident. No: 57104			
								Date: July 15, 2004					Specification No.: F00165-X
UNCONTROLLED DOCUMENT A later revision of this specification may exist.							 A member of The Marmon Group of companies		Size: A	Scale: ---	Page: 1 of 1	Rev. ---	