			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>'SPECIFICATION</u>		7/6/2010	В	#13004	SPECIFICATION UPDATED
<u>Parent Number:</u> <u>Description:</u>	F18369- 18 Solid TC AWM 3071/3231 SF-2 SEW-2 Braided Silicone	DIAMETER: (TOLERANCE ± : (
	<u>18 SOLID TC</u> UL: AWM 3071/3231 SF-2 CSA: SEW-2			•	M	VIN AVERAGE WALL: <u>0.030</u> MINIMUM WALL: <u>0.027</u>
Insulation:	Braided Silicone					
<u>Print Legend:</u>	18 AWG (0.823mm2) E22337 (PLANT ID CODE) (UL) TYPE SF-2 OR AWM 3071/3231 200C 600V 156016 CSA SEW-2 200C 600V FT1					
<u>Voltage:</u> <u>Temperature:</u> <u>Notes:</u>	200C 1. Diameter shown is OD under braid.					
1. The OD over the braid is approximately 0.113". The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.				any party	CO	LEMAN CABLE, INC
	* Nbr(s):				1530 SM	nields Drive gan, IL 60085
		y Name:				1-000-323-9333
<i>i iile</i>	Compan_	y 11ume			www.col	emancable.com