			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>SPECIFICATION</u>		7/6/2010	G	#13004	SPECIFICATION UPDATED
<u>Parent Number:</u> <u>Description:</u>	F18096- 18 7/.0152 TC AWM 3071/3231 SF-2 SEW-2 Braided Silicone	DIAMETER: (TOLERANCE ± : (
<u>Stranding:</u>	7/.0152 TC LHL				M	▼ // IN AVERAGE WALL: <u>0.030</u>
<u>Style:</u>	UL: AWM 3071/3231 SF-2 CSA: SEW-2					MINIMUM WALL: 0.027
	Braided Silicone 18 AWG (0.823mm2) E22337 (PLANT ID CODE) (UL) TY	PE SF-2 OR AWM 3071/	3231 200C (600V 15	6016 CSA	SEW-2 200C 600V FT1
<u>Voltage:</u> <u>Temperature:</u>						
<u>Notes:</u>	 Diameter shown is OD under braid. The OD over the braid is approximately 0.116". 					
This product complies with European Directive 2011/65/EU (RoHS 2) The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is p without written conser	roprietary intellectual property of Coleman Cable. Any information on to f Coleman Cable.	contained herein shall not be	e disclosed to	any party	CO	LEMAN CABLE, INC
Customer Approval:						nields Drive
Customer Part Nbr(s):					Waukeg	gan, IL 60085
	Date:					1-000-323-9333
Title:_	Company	Name:			www.col	emancable.com